

# TRITON E

signsfy  
SIGN WAREHOUSE



Printhead Precision Core Epson I3200



## Parameters

### SID TRITON 180ES


### SID TRITON 320ES

### SID TRITON 320ESX

<b>Printhead Epson I3200</b>	3200 nozzles • Variable dots • 3.8 • 6 • 12 picoliters			
<b>Number of printheads</b>	2	2	4	
<b>Resolution</b>	Up to 2880 dpi			
<b>Ink</b>	4 colors (CMYK) - Eco-Solvent - 1 liter per color			
<b>Media</b>				
<b>Max. printing width</b>	126" (3,200 mm)			
<b>Max. media width</b>	129" (3,300 mm)			
<b>Feeding System</b>	Roll or sheet			
<b>Take Up System</b>	Included			
<b>Print Mode</b>	Quality	280 sq.ft./h (26 m <sup>2</sup> /h)	559 sq.ft./h (52 m <sup>2</sup> /h)	1119 sq.ft./h (104 m <sup>2</sup> /h)
	High Quality	183 sq.ft./h (17 m <sup>2</sup> /h)	366 sq.ft./h (34 m <sup>2</sup> /h)	731 sq.ft./h (68 m <sup>2</sup> /h)
	Backlit	140 sq.ft./h (13 m <sup>2</sup> /h)	280 sq.ft./h (26 m <sup>2</sup> /h)	560 sq.ft./h (52 m <sup>2</sup> /h)
<b>X direction configuration</b>	Steel Strip and bearing	Steel Strip and bearing	Linear Rail	
<b>Cleaning System</b>	Auto cleaning			
<b>Heating and Cooling System</b>	Preheater, middle and front heaters and cooling fans			
<b>Interface</b>	High Speed Ethernet			
<b>Maximum Carriage Height</b>	Up to 0.08" (2mm)			
<b>Rip Software</b>	PhotoPrint OEM or FlexiPrint 21 Optional			
<b>Voltage</b>	AC 220V, 50Hz / 60Hz			
<b>Power Consumption</b>	Printer: 220W (2A) Heater: 3,150W (14A)	Printer: 220W (2A) Heater: 5,900W (23A)	Printer: 720W (3.3A) Heater: 9,200W (42A)	
<b>Operational Temperature</b>	68°F - 77° F (20°C - 25°C) Humidity 40 - 60%, non condensing			
<b>Printer Dimensions (Length x Width x Height)</b>	(3,080 x 710 x 1,420 mm) 121"x 28"x 56"	(4,480 x 760 x 1,420 mm) 177"x 30"x 56"	(4,680 x 840 x 1,460 mm) 184"x 33"x 48"	
<b>Package Dimensions (Length x Width x Height)</b>	(3,190 x 740 x 845 mm) 126"x 29"x 33"	(4,590 x 740 x 940 mm) 181"x 29"x 37"	(4,800 x 1,000 x 940 mm) 189"x 40"x 37"	
<b>Printer weight</b>	450 lbs (204 kg)	534 lbs (242 kg)	758 lbs (344 kg)	
<b>Package weight</b>	840 lbs (381 kg)	977 lbs (443 kg)	1,294 lbs (587 kg)	




Cartridges



Capping Station



Feeding Brackets



Pinch Roller



Control Panel



Dist Sagaró de México, S.A. de C.V.  
Equipos y Materiales para Impresión Digital de Gran Formato  
Tel. 01 (55) 5617 2599 01800-718-5600  
[www.sagaró.com.mx](http://www.sagaró.com.mx) [contacto@sagaró.com.mx](mailto:contacto@sagaró.com.mx)



Contáctanos via WhatsApp  
55 5338 5891

